

Belite 254 Inventory Listing

This is not a kit. Fly Away Factory, FOB Wichita, KS

SPECIFICATIONS FOR: Serial # 09080200BA

MORE PICTURES AT <http://www.flickr.com/photos/beliteaircraft/>



GENERAL

- Flying Weight, 242 pounds as listed. Ultralight FAR 103 compliant.
- THIS AIRCRAFT IS COMPLETE AND READY TO FLY.
- VERIFICATION SUBJECT TO BUYER'S INSPECTION.
- SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- THIS AIRCRAFT SUBJECT TO PRIOR SALE.
- YOU MUST READ, UNDERSTAND, AND SIGN A PURCHASING AGREEMENT PRIOR TO SALE.

AIRFRAME

- Easy folding wings – one person, as little as 5 minutes
- Complete 4130 aircraft steel welded fuselage, black
- Carbon Fiber / Aluminum lift struts
- Dacron fabric with orange paint
- 2.5 inch tubular aluminum main spars, two per wing
- One piece acrylic windshield, includes top of cabin

FIREWALL FORWARD

- Carbon Fiber firewall
- MZ34 28HP engine
- Tennessee Propeller 60 x 19 wooden prop
- Electronic Ignition
- Electric Start
- 12V Sealed Lead Acid starting battery
- Cowling (to be installed at later date after vendor delivery, it flies just fine without it)
- Alternator
- Voltage Regulator
- Starter relay
- Starter switch (mounted in panel)
- Primer (mounted in panel)
- Ignition kill switch (mounted in panel)

FUEL SYSTEM

- 5 gallon tank
- Electronic capacitive fuel sender
- Inline fuel filter
- Fuel on/off switch
- Fuel Quantity electric gauge (mounted in panel)

STANDARD PANEL

- Wood panel, stained and varnished – looks gorgeous
- Panel shock mounts (3)
- Airspeed Indicator
- Altimeter
- Inclinator (ball)
- EGT / CHT
- Fuel Quantity (Electronic)
- Starter Switch
- Ignition kill switch
- Tach/Hour Meter
- Primer

LANDING GEAR

- Solid (bolted) gear assembly, ready to accept bungees. (Bungees not included)
- Azusa nylon wheels, 5 inch
- Mechanical brakes
- Lamb 5 inch tires
- Full swivel ball bearing mounted steerable tail wheel

FLIGHT CONTROLS AND INTERIOR

- Control Stick
- Push pull aluminum tube to elevator, with steel bellcranks, rod end bearings, and nylon bushing bearing
- Rudder pedals
- Cable operated Rudder with 3/32 stainless steel cable
- 4 point lap and shoulder harness
- Varnished birch plywood seat bottom, seat back, floorboard
- Heel brakes (mechanical)
- Flap handle with 4 settings (0, 1, 2, 3 notches)

SAFETY FEATURES

- 4 point lap and shoulder harness
- Complete 4130 reinforced fuselage
- Full 360 degree visibility